


Single Stage Electric

8-Gallon

Designed and manufactured to the same stringent quality standards as all Mi-T-M equipment this air compressor offers maximum efficiency and flexibility. The industrial electric motor features an auto start/stop and a 10-inch fly wheel for extra cooling and longer life.



Compressor Pump

- Quality cast iron single stage compressor
- Splash lubricated cast iron crankcase to extend the hours of performance
- Cast iron head for heat dissipation
- Stainless-steel braided discharge hose
- Large canister intake filter

Motor

- Industrial-UL listed electric motor
- Auto start/stop (continuous run optional)
- Thermal overload motor protection

Frame

- Powder coated 8-gallon twin tank receivers
- 3/16-inch base plate to reduce vibration
- 14-gauge powder coated two-piece belt guard with 1/4-turn release for quick access to belts
- Convenient lifting handles
- Pneumatic tire with tube and steel hub

Components

- Regulator and two gauges for tank and outlet pressure
- Manual drain valves for proper maintenance
- Belt tightening system pulls motor straight to ensure constant belt alignment
- 10-inch fly wheel for extra cooling and longer life
- Industrial-grade pressure switch

Warranties



Model Number	CFM @ PSI	HP/Motor	Plug Type	Dimensions (LxWxH)	Ship Wt.	Net Wt.
AM1-PE15-08M	6.5 @ 100	1.5 HP, 120V, 13.2A	NEMA 5-15P	44.5in.x18.5in.x25in.	190 lbs.	170 lbs.
AM1-PE02-08M	8.4 @ 100	2.0 HP, 120V, 18.8A	NEMA 5-20P	44.5in.x18.5in.x25in.	190 lbs.	170 lbs.

OPTIONS

Part Number	Description	Fits Models
AX-0002	Auto drain plastic bowl - Drains moisture from air system	All models
AX-0003	Manual drain metal bowl - Drains moisture from air system	All models
AX-0005	Dual control - Compressor can be operated in start/stop mode or continuous run where pilot valve exhausts air to atmosphere	All models
TX-1001-W	Puncture-proof tire - Tire is flat-free, maintenance-free, 10-inch, white hub, one tire	All models