



# FLOOR GRINDING SURFACE PREPARATION

Concrete Grinders have been setting the standards in surface preparation, repair and restoration for over 50 years!!

## NEW Dual-Disc Floor Grinder

MODEL #	PART #	POWER	HORSE POWER	PHASE	AMPS	*RPM's	BELTS	LENGTH	WIDTH	HEIGHT	WEIGHT
2EC-NG-1.5	59200	Electric	1.5 HP, 115/230 V	Single	16/8	231	Std "V" Belt	46"	27"	37"	258 lbs
2GC-NG-11H	59300	Gasoline	**11 HP	NA	NA	562	Std "V" Belt	46"	27"	37"	282 lbs

**PRODUCTION RATE:** 22" Working Width will grind approximately 400 - 500 Sq. ft. per hour at 1/32" with EDCO Dyma-Serts™

**INCLUDES:** 2 - New Slide-On Multi-Accessory Discs, which accept Dyma-Serts, Strip-Serts and all other Quick-Change accessories, 2" - 3" Multi-Vacuum Port and Wa Port, Electric models have a 115/230 Voltage Selector Switch

**REQUIRES:** 6 - Grinding Accessories required per loading

**IDEAL FOR:** Production grinding and floor cleaning on large or small surface areas such as airports, warehouses, parking decks, manufacturing plants, malls and sports arenas • Light grinding or cleaning of concrete surfaces • Leveling uneven joints • Removing mastics, thin-set, high spots, epoxies and urethanes • Lightly texturing slippery concrete surfaces



**Weight Blocks**  
40 LBs each, 2 required  
**Part # 77506**



**PCDyma-SERTS**  
4 times stronger than carbide with incredible removal capabilities



**Dyma-SERTS**  
5 times faster than grinding stones. Long Lasting!



**STRIP-SERTS**  
Removes surface build-ups without grinding into the surface below

**Magnetic Quick-Change Multi-Accessory Disc is quick change technology - Change accessories in less than 30 seconds, accessories slide on and off, no tools required!**

## Wedge-Less Floor Grinder Accessories

### Wedge-Less PCDyma-Serts™ - Holding Case Part # 19361

Make quick work of Epoxy Coatings & Hard Glue. Four times stronger than carbides, with remarkable resistance.

**Ideal for the removal of:** Hard Tacky Surfaces, Urethane Epoxy, Multi-Part Epoxy, Water-Proofing Membrane, Pool Deck Coating, Thick Mastics, Old and New Epoxy Coatings.

### Wedge-Less Dyma-Serts - Holding Case Part # 19361

Dyma Serts grind 5 times faster than grinding stones and last longer - up to 30,000 sq ft (2,800 sq m) of grinding action on standard 3,500 PDI concrete. Dyma-Serts can be used for wet or dry grinding

**Ideal for the removal of:** Smoothing rough surfaces or trowel marks, grinding terrazzo, repairing surface damage to concrete slabs, Removing urethane or epoxy thincoats, Grinding sharp aggregates such as flint and granite, removing surface imperfections from epoxy mortars, leveling high spots, removing thin mastics and thin-set

### Wedge-Less Strip-Serts - Holding Case (Left Hand) Part # 12425, Holding Case (Right Hand) Part # 12421

Strip-Serts are carbide tipped blocks designed to clean floors without grinding into the concrete. Strip-Serts have a replaceable, multi-sided tungsten carbide edge that can be rotated for maximum use.

**Ideal for the removal of:** Removing mastics, paints, resins, tar, fiberglass, ice and industrial buildups.

\*\* Call for availability.

\* RPM's are based on the machine's accessory speed.

\* **NET HORSEPOWER STATEMENT** - \*As rated by the engine manufacturer. The power rating of the engine indicated in this document is the net power output tested on a production engine for the engine model and measured in accordance with SAE j1349 at 3600 rpm. Mass production engines may vary from this value. Actual power output for the engine installed in the final machine will vary depending on numerous factors, including the opening speed of the engine in application, environmental conditions, maintenance, and other variables.